



PROTECT MARK

**THE ONLY PAINT THAT DOES NOT CONTAIN
CARCINOGENIC, MUTAGENIC, OR TOXIC
COMPONENTS FOR REPRODUCTION**

UNIQUE AND PATENTED SAFETY CAP :

- The only locking cap
- A particularly robust safety cap (a full aerosol dropped from a height of 1.50m will remain intact)
- No contact with the paint

**CLEAR VARNISH EXTENDS THE DURA-
TION OF MARKING PAINT OR CHALK LINE**

**PAINTS THAT RESPECT MEN AND THE
ENVIRONMENT**

100% USAGE GUARANTEE, NO WASTE


CAN BE USED UP TO -15°C

UV AND MECHANICAL PROTECTION


ONLY 3 PICTOGRAMS !



1 COLOUR AVAILABLE



INSTRUCTIONS FOR USE



1. Before use : Shake vigorously
2. Unlock the aerosol by turning left the safety cap
3. Use PROTECT MARK about 10cm from the support
4. After use, DO NOT PURGE (valve multidirectional)
5. Lock the aerosol by turning right the safety cap

HEATH AND SAFETY :


Consult our free safety data sheets on our website www.soppec-inc.com

No paint mist or drips during use


GHS labelling with three pictograms



Carton
Box



Palette Nimp15
100 x 120 cm



76 boxes per pallet of
12 aerosols

SAFETY CAP

PROTECT MARK is fitted with the patented Soppec «TP» safety cap. The unique design of this cap gives it the following advantages:

- Protection against accidental tripping during transport or handling
- Protection of the user's hands against painting projections
- Easy to use
- The strongest safety cap on the market : No break when a full aerosol falls 1.50m (Test carried out on asphalt)
- A fine and precise spray which allows the realization of clear markings
- Cap denotes colour of the paint.

PROPRIÉTÉS

Colorless

Drying time : About 5 minutes at 20°C

Ideal storage between 15 to 25°C, do not freeze

Shelf life: 4 years warranty

Usable with the gun handle and the one-wheel applicator

GENERAL CONDITIONS

- Do not expose to temperatures above 50°C
- Keep away from sources of ignition, heat and sunlight
- Do not smoke
- Do not pierce even after use the aerosol
- Do not burn even after use the aerosol